

Connected Load:	Lumen output:	Luminous efficacy:	Measurements:
15 Watt	1500lm	100lm/W	Ø147.6xH120mm
20 Watt	2000lm	100lm/W	Ø176.6xH130mm
28 Watt	2800lm	100lm/W	Ø232xH160mm
24-32Watt	3200lm	100lm/W	Ø232xH160mm
28-35Watt	3500lm	100lm/W	Ø232xH160mm

Mounting: surface mounted
Color temperature: 3000/4000/6000 Kelvin
Color Rendering Index: >80
Power factor: >0.95
Beam angle: 60°
LED chip: TRIAC
Driver: Flash-Free led driver
Dimmable: on request DALI/1-10V/TRIAC
Mains voltage: 220-240V
Mains frequency: 50-60Hz
Material: die-cast aluminum
IP class: IP20
Lifespan: 50.000 hours L90/B50 (T_q 25°C)
 48.000 hours L70/B50 (T_q 25°C)
Warranty: 3 years



www.doublelux.nl

Double Lux Lighting B.V. Nijverheidsweg 2 9902 AE Appingedam The Netherlands **T** +31 (0)596 620075 **E** info@doublelux.nl

All technical data have been compiled with all due care, errors excepted.
 Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in our products.