

Connected Load:	Lumen output:	Luminous efficacy:	Measurements:	Weight:
40 Watt	5000lm	125lm/W	1200x92x74mm	2.3 kg
60 Watt	7500lm	125lm/W	1500x92x74mm	2.5 kg

Mounting:	surface mounted (quick fix brackets for ceiling/wall mounting included) suspended (with optional max 1500mm suspension set)
Color temperature:	4000/5000 Kelvin
Color Rendering Index:	>80
Power factor:	>0.95
Beam angle:	120°
LED chip:	integrated led SMD 2835
Dimmable:	no
Mains voltage:	220-240V
Mains frequency:	50-60Hz
Ambient temperature:	-15° - +35°C
Material:	aluminum
Diffuser:	polycarbonate, opal
Luminaire color:	grey
IP class:	IP65
Impact resistance:	IK10
Lifespan:	60.000 hours L70/B50 (T _q 25°C)
Warranty:	3 years



Through wiring standard

www.doublelux.nl

Double Lux Lighting B.V. Nijverheidsweg 2 9902 AE Appingedam The Netherlands **T** +31 (0)596 620075 **E** info@doublelux.nl

All technical data have been compiled with all due care, errors excepted.
 Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in our products.