



	100 Watt	200 Watt	300 Watt	400 Watt	600 Watt
<b>Measurements:</b>	226x183x102mm	230x242x194mm	340x242x194mm	422x243x221mm	422x243x336mm
<b>Mounting:</b>	Surface mounted (bracket)	Surface mounted (bracket)	Surface mounted (bracket)	Surface mounted (bracket)	Surface mounted (bracket)
<b>Color temperature:</b>	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
<b>Lumen output:</b>	ca. 14.000lm	ca. 28.000lm	ca. 42.000lm	ca. 56.000lm	ca. 84.000lm
<b>Power consumption:</b>	ca. 100W	ca. 200W	ca. 300W	ca. 400W	ca. 600W
<b>Lm/W(led):</b>	170-180Lm/W	170-180Lm/W	170-180Lm/W	170-180Lm/W	170-180Lm/W
<b>Lm/W (fixture):</b>	ca. 140 Lm/W	ca. 140 Lm/W	ca. 140 Lm/W	ca. 140 Lm/W	ca. 140 Lm/W
<b>LED chip:</b>	Philips Lumiled	Philips Lumiled	Philips Lumiled	Philips Lumiled	Philips Lumiled
<b>Driver:</b>	Mean Well	Mean Well	Mean Well	Mean Well	Mean Well
<b>Powerfactor:</b>	>0.95	>0.95	>0.95	>0.95	>0.95
<b>Color rendering CRI:</b>	≥ 80	≥ 80	≥ 80	≥ 80	≥ 80
<b>Beam angle:</b>	10/25/70/120°	10/25/70/120°	10/25/70/120°	10/25/70/120°	10/25/70/120°
<b>Material:</b>	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
<b>Working temperature:</b>	-40°C+60°C	-40°C+60°C	-40°C+60°C	-40°C+60°C	-40°C+60°C
<b>Power:</b>	AC 90-277V 50/60Hz	AC 90-277V 50/60Hz	AC 90-277V 50/60Hz	AC 90-277V 50/60Hz	AC 90-277V 50/60Hz
<b>Weight:</b>	ca. 2.8 Kg	ca. 4.1 Kg	ca. 5.6 Kg	ca. 7.6 Kg	ca. 10.5 Kg
<b>IP Class:</b>	IP65	IP65	IP65	IP65	IP65
<b>Lifespan:</b>	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs
<b>Warranty:</b>	3 years	3 years	3 years	3 years	3 years
<b>Certificate:</b>	CE- RoHS	CE- RoHS	CE- RoHS	CE- RoHS	CE- RoHS



100W



200W



300W



400W



600W