



	240 Watt	360 Watt	480 Watt	720 Watt	960 Watt
Measurements:	436x341x190mm	619x341x200mm	580x442x201mm	834x442x201mm	1090x442x201mm
Mounting:	Surface mounted (bracket 180° rotatable)	Surface mounted (bracket 180° rotatable)	Surface mounted (bracket 180° rotatable)	Surface mounted (bracket 180° rotatable)	Surface mounted (bracket 180° rotatable)
Color temperature:	3000-3500K 4000-4500K 5000-6500K	3000-3500K 4000-4500K 5000-6500K	3000-3500K 4000-4500K 5000-6500K	3000-3500K 4000-4500K 5000-6500K	3000-3500K 4000-4500K 5000-6500K
Lumen output:	ca. 27.600lm 60x100° ca. 30.000lm 120°	ca. 41400lm 60x100° ca. 45.000lm 120°	ca. 55200lm 60x100° ca. 60.000lm 120°	ca. 82800lm 60x100° ca. 90.000lm 120°	ca. 110.400lm 60x100° ca. 110.000lm 120°
Power consumption:	ca. 245W	ca. 367W	ca. 489W	ca. 737W	ca. 978W
LED chip:	Philips Lumileds	Philips Lumileds	Philips Lumileds	Philips Lumileds	Philips Lumileds
Driver:	Mean Well	Mean Well	Mean Well	Mean Well	Mean Well
Powerfactor:	>0.9	>0.9	>0.9	>0.9	>0.9
Color rendering CRI:	≥ 80	≥ 80	≥ 80	≥ 80	≥ 80
Beam angle:	60x100° / 120°	60x100° / 120°	60x100° / 120°	60x100° / 120°	60x100° / 120°
Material:	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Working temperature:	-20°C+50°C	-20°C+50°C	-20°C+50°C	-20°C+50°C	-20°C+50°C
Power:	AC 100-277V 50/60Hz	AC 100-277V 50/60Hz	AC 100-277V 50/60Hz	AC 100-277V 50/60Hz	AC 100-277V 50/60Hz
Weight:	ca. 12.3 Kg	ca. 16.1 Kg	ca. 20.3 Kg	ca. 31.1 Kg	ca. 38 Kg
IP Class:	IP65	IP65	IP65	IP65	IP65
Lifespan:	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs
Warranty:	3 years	3 years	3 years	3 years	3 years
Certificate:	CE- RoHS	CE- RoHS	CE- RoHS	CE- RoHS	CE- RoHS



240W



360W



480W



720W



960W