



	80 Watt	120 Watt	150 Watt	200 Watt	300 Watt
Measurements:	477x160 mm	484x200 mm	494x200 mm	524x200 mm	594x240mm
Mounting:	Hook	Hook	Hook	Hook	Hook
Colour temperature:	5500K	5500K	5500K	5500K	5500K
Lumen output:	ca. 8000lm	ca. 12.000lm	ca. 15.000lm	ca. 20.000lm	ca. 29.000lm
Beam angle:	45/120°	45/120°	45/120°	45/120°	45/120°
Power consumption:	89W	132W	162W	218W	325W
LED chip:	Bridgelux	Bridgelux	Bridgelux	Bridgelux	Bridgelux
Driver:	Meanwell	Meanwell	Meanwell	Meanwell	Meanwell
Powerfactor:	>0.95	>0.95	>0.95	>0.95	>0.95
Dimmable:	Optional	Optional	Optional	Optional	Optional
Color rendering CRI:	>80	>80	>80	>80	>80
Weight:	ca. 6.2 kg	ca. 7.8 kg	ca. 9.3 kg	ca. 9.9 kg	ca. 16.8 kg
Material:	Anodised aluminium/Steel	Anodised aluminium/Steel	Anodised aluminium/Steel	Anodised aluminium/Steel	Anodised aluminium/Steel
Working temperature:	-40°C+55°C	-40°C+55°C	-40°C+55°C	-40°C+55°C	-40°C+55°C
Power:	AC 85-265V	AC 85-265V	AC 85-265V	AC 85-265V	AC 85-265V
IP Class:	IP65	IP65	IP65	IP65	IP65
Lifespan:	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs
Warranty:	3 years	3 years	3 years	3 years	3 years