



	50 Watt	100 Watt	150 Watt	200 Watt	300 Watt
Measurements:	242x102x197 mm	242x221x247 mm	242x340x247 mm	419x221x247 mm	419x340x247mm
Mounting:	Bracket	Bracket	Bracket	Bracket	Bracket
Colour temperature:	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Lumen output:	ca. 6000lm	ca. 12.000lm	ca. 18.000lm	ca. 24.000lm	ca. 36.000lm
Beam angle:	30/60/110°	30/60/110°	30/60/110°	30/60/110°	30/60/110°
Power consumption:	50W	100W	150W	200W	300W
LED chip:	Philips Lumileds	Philips Lumileds	Philips Lumileds	Philips Lumileds	Philips Lumileds
Driver:	Meanwell	Meanwell	Meanwell	Meanwell	Meanwell
Powerfactor:	>0.95	>0.95	>0.95	>0.95	>0.95
Dimmable:	Optional	Optional	Optional	Optional	Optional
Color rendering CRI:	>80	>80	>80	>80	>80
Weight:	ca. 2.1 kg	ca. 3.2 kg	ca. 4.1 kg	ca. 5.5 kg	ca. 7.5 kg
Material:	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Working temperature:	-40°C-+60°C	-40°C-+60°C	-40°C-+60°C	-40°C-+60°C	-40°C-+60°C
Power:	AC 85-265V	AC 85-265V	AC 85-265V	AC 85-265V	AC 85-265V
IP Class:	IP65	IP65	IP65	IP65	IP65
Lifespan:	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs	50.000 hrs
Warranty:	3 years	3 years	3 years	3 years	3 years



50W

100W

150W

200W

300W