

Connected Load:	Lumen output:	Luminous efficacy:	Measurements:	Weight:
36 Watt	4320lm	120lm/W	600x600x9mm	4 kg
36 Watt	4320lm	120lm/W	1200x300x11,3mm	4 kg

**Mounting:** recessed/surface mounted/suspended  
**Color temperature:** 3000/4000/5500/6000 Kelvin  
**Color Rendering Index:** >80  
**Powerfaktor:** 0.95  
**Beam angle:** diffuse light  
**UGR:** <19  
**LED chip:** 4014  
**Driver:** standard / Flicker Free on request  
**Dimmable:** on request 1-10V / Dali / Triac  
**Mains voltage:** 200-240 VAC  
**Mains frequency:** 50-60Hz  
**Material:** frame aluminum, cover PMMA  
**Luminaire color:** white  
**IP class:** IP20  
**Lifespan:** 50.000 hours L70  
**Warranty:** 3 years  
**Optional:** suspension set  
 KIT for surface mounting



[www.doublelux.nl](http://www.doublelux.nl)

Double Lux Lighting B.V. Nijverheidsweg 2 9902 AE Appingedam The Netherlands T +31 (0)596 620075 E info@doublelux.nl

All technical data have been compiled with all due care, errors excepted.  
 Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in our products.