

Connected Load:	Lumen output:	Luminous efficacy:	Measurements:	Weight:
24 Watt	2880lm	120lm/W	600x70x68mm	1 kg
36 Watt	4320lm	120lm/W	1200x70x68mm	1.5 kg
50 Watt	6000lm	120lm/W	1500x70x68mm	2.5 kg

Mounting:	surface mounted (quick fix brackets for ceiling/wall mounting included)
Color temperature:	4000 Kelvin
Color Rendering Index:	>80
Beam angle:	120°
LED chip:	integrated LED strip
Driver:	Osram
Dimmable:	no
Mains voltage:	220-240V
Mains frequency:	50-60Hz
Ambient temperature:	-25° - +30°C
Material:	polycarbonate
Diffuser:	polycarbonate
Luminaire color:	grey
IP class:	IP65
Lifespan:	NL/EIA 2021 50.000 hours L90/B50 (T _q 25°)
Warranty:	2 years

QUICK[®]
EASY
 INSTALLATION



through wiring standard

www.doublelux.nl

Double Lux Lighting B.V. Nijverheidsweg 2 9902 AE Appingedam The Netherlands T +31 (0)596 620075 E info@doublelux.nl

All technical data have been compiled with all due care, errors excepted.
 Product illustrations serve as examples and may differ from the original. We reserve the right to make alterations in our products.