

| Connected Load: | Lumen output: | Luminous efficacy: | Measurements: | Weight: |
|-----------------|---------------|--------------------|---------------|---------|
| 166 Watt | 28.000lm | 169lm/W | Ø450mm | 7.2 kg |
| 197 Watt | 32.000lm | 162lm/W | Ø450mm | 7.2 kg |
| 226 Watt | 36.000lm | 159lm/W | Ø450mm | 7.2 kg |

| | |
|-------------------------------|---|
| Mounting: | suspended |
| Color temperature: | 5700 Kelvin (4000 Kelvin on request) |
| Color Rendering Index: | >80 |
| Color tolerance: | 3 SDCM |
| Powerfaktor: | >0.98 |
| Beam angle: | 113° (75° on request) |
| LED chip: | Lumiled |
| Dimmable: | Dali dimmable (standard) |
| Mains voltage: | 230V |
| Inrush current: | Zero inrush |
| Ambient temperature: | -30° - +50°C |
| Material: | die-cast aluminum, tempered glass |
| Luminaire color: | industrial grey |
| IP class: | IP67 |
| Impact resistance: | IK07 (tempered glass) IK08 (PMMA) |
| Lifespan: | 50.000 hours L90/B50 (T _q 25°) 100.000 hours L70/B50 (T _q 25°) NL/EIA 2022 - luminous flux conform LM 79-19 |
| Warranty: | 5 years |

